

OVIA™ ATM10 Series Cash Dispenser ATM



ATM10 series is a new global cash dispenser ATM of OVIA™. It delivers values with its simplicity, security, reliability, convenience beyond customer's expectations.

Compact Design

- Ergonomic and compact design.
- Minimization of installation space and small foot-print.
- Lobby Type Dimension :
450mm x 715mm x 1392mm (W x D x H)
- TTW Type Dimension :
650mm x 991mm x 1817mm (W x D x H)

High Security Features

- Adoption of international standard safe (UL 291 Level 1)
- Double locking system (Dial & Key lock)
- Various Security Camera option (Face, Wrist, Safe Camera)
- Anti Skimmer and Security Mirror.
- PCI Compliant EPP.
- Anchor Bolting to prevent a unit from moving.

Maximized Usability

- Easy to use UI (User Interface).
- Multi Touch Screen



*ATM11 (front service)



ATM10 Series Technical Information

Servicing	ATM10 ATM11	Rear Service (TTW) Front Service (Lobby)
Customer Interface	Display	15" color LCD with 8 function keys (Option: Touch Screen, sunlight viewable, privacy filter)
	Card Reader	EMV Certified Smart Motorized MS/IC with retract capability (Option: AntiSkimming)
	Keyboard	PCI Certified EPP, 3-DES
	Other	Flicker on all entry/exit points, Speaker, Audio Jack
Operator Panel	Display	15.6" color LCD Touch Display (ATM10 TTW only)
Cash Dispensing Module	4 dispensing cassettes (3,000 notes / cassette)	
	1 Reject/Retract cassette (two compartments, 250+250 notes)	
	Maximum transaction volume : 100 notes	
	Cash handling speed : 7~8 notes/sec	
Printers	Receipt	Thermal printer (80mm, 220 Ø)
	Journal	Electronic journal (Option: Thermal printer 80mm 220 Ø)
Security Features	Camera	Face, Wrist, (Option: Safe)
	UPS	Capacitor, (Option: Battery)
	Safe	UL291 Level 1 (Option: CEN L, CEN III)
	Lock	Dial lock + Key lock (long key)
Main Control Unit	Industrial PC	Intel Core i5, RAM 4GB, HDD 500G, DVD-ROM(option)
Software	Windows 7 (Windows 10 migration) , CEN/XFS 3.0	
Power Supply	200-240VAC (50/60Hz)	
Dimensions / Weight (WxDxH, mm) /(Net, kg)	ATM10	450 x 715 x 1,392 mm / ~425 kg
	ATM11	650 x 991 x 1,817 mm / ~400 kg
Environment	Temperature	5~40°C (operation) / -20~60°C (storage)
	Humidity	20~80% (operation) / 10~90% (storage)
Other Options	2D Barcode reader, Contactless IC Card, RFID/NFC, Beacon, Anti-skimming, Biometric reader, Temperature/Humidity Sensor, Vibration Sensor,	

* Specifications are subject to change without notice.